



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

**DEFENDER AP70 PART A
SAFETY DATA SHEET**

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	DEFENDER AP70 SIDE A
REVISION DATE	JUNE 2025
MANUFACTURER'S NAME	UMI COATINGS
ADDRESS	2870 CRESTWOOD BLVD. STE B IRONDALE, AL 35210
EMERGENCY PHONE	CHEMTREC: 800-424-9300 (ACCOUNT: CCN1022026)
INFORMATION PHONE NUMBER	205-857-0040

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS):

Health, Respiratory or skin sensitization, 1 Respiratory
Health, Respiratory or skin sensitization, 1 Skin
Health, Skin corrosion/irritation, 2
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Specific target organ toxicity - Single exposure, 3
Health, Acute toxicity, 5 Inhalation
Environmental, Hazards to the aquatic environment - Acute, 2

GH LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

GHS SIGNAL WORD: **DANGER**

GHS HAZARD PICTOGRAMS:





2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART A
SAFETY DATA SHEET

GHS HAZARD STATEMENTS

- H334** May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H317** May cause an allergic skin reaction
- H315** Causes skin irritation
- H319** Causes serious eye irritation
- H336** May cause drowsiness or dizziness
- H333** May be harmful if inhaled
- H401** Toxic to aquatic life

GHS PRECAUTIONARY STATEMENTS

- P261** Avoid breathing dust/fume/gas/mist/vapors/spray.
- P264** Wash hands thoroughly after handling.
- P271** Use only outdoors or in a well-ventilated area.
- P272** Contaminated work clothing should not be allowed out of the workplace.
- P273** Avoid release to the environment. **P280** - Wear protective gloves/protective clothing/eye protection/face protection.
- P284** Wear respiratory protection.
- P302+352** IF ON SKIN: Wash with soap and water.
- P304+340** IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338** IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P310** Immediately call a POISON CENTER or doctor/physician.
- P333+313** If skin irritation or a rash occurs: Get medical advice/attention.
- P337+313** Get medical advice/attention.
- P342+311** Call a POISON CENTER or doctor/physician.
- P362** Take off contaminated clothing and wash before reuse.
- P403+P233** Store in a well ventilated place. Keep container tightly closed.
- P405** Store locked up.
- P501** Dispose of contents/container to a licensed waste disposal company.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS

Route of Entry Eyes; Ingestion; Inhalation; Skin

Target Organs Respiratory system; Skin; Eyes

Inhalation At room temperature, MDI vapors are minimal due to low vapor pressure. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals. Impaired lung function has been associated with overexposure to isocyanates. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Heating, spraying, foaming or otherwise mechanically dispersing operations may generate vapor or aerosol concentrations sufficient to cause irritation or other adverse effects.



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

**DEFENDER AP70 PART A
SAFETY DATA SHEET**

- Skin Contact** Prolonged or repeated exposure can cause skin irritation, reddening, dermatitis and in some cases sensitization. Skin contact may result in allergic reactions or respiratory sensitization, but it is not expected to result in absorption of amounts sufficient to cause other adverse effects. May stain skin.
- Eye Contact** As a liquid or dust, may cause irritation, inflammation, and/or damage to sensitive eye tissue. Symptoms include watering or discomfort of the eyes. Corneal injury is unlikely. As a liquid or dust, may cause irritation, inflammation, and/or damage to sensitive eye tissue. Symptoms include watering or discomfort of the eyes. Corneal injury is unlikely.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

CAS	CHEMICAL NAME	% BY WEIGHT
5124-30-1	Methylene bis(4-cyclohexylisocyanate)	30-40%
0	Aliphatic isocyanate prepolymer blend	55-60

SECTION 4. FIRST AID MEASURES

INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility immediately. Get immediate medical attention.

SKIN CONTACT

Wash off in flowing warm water or shower with soap. Remove and wash contaminated clothing. Properly dispose of any articles that cannot be decontaminated, like leather belts. If redness, burning or itching develops or persists after the area has been washed, consult a physician.

EYE CONTACT

Flush with large amounts of water for 15 minutes. Materials containing MDI may react with the moisture in the eye forming a thick material that is difficult to remove. Get immediate medical attention.

INGESTION

Do not induce vomiting or give liquids unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

- Flammability: OSHA - none; DOT - none
- Flash Point: >250°F
- Flash Points Method: COC
- Burning Rate: N/A
- Autoignition Temp: N/A
- LEL: N/A
- UEL: N/A



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART A
SAFETY DATA SHEET

Use dry chemical, foam, carbon dioxide, or halogenated agents. If water is used, use very large quantities. The reaction between water and hot isocyanate may be vigorous. If possible, contain fire run-off water.

Protective Equipment: Wear positive-pressure self-contained breathing apparatus with full face mask and full protective clothing.

Unusual Hazards: At temperatures greater than 400°F, polymeric MDI can polymerize and decompose which will cause pressure build-up in closed containers. Explosive rupture is possible. Water contamination will produce carbon dioxide. Do not reseal contaminated containers as pressure buildup may rupture the containers. Downwind personnel must be evacuated.

Fire Degradation Products: Isocyanate vapor and mist, carbon dioxide, carbon monoxide, nitrogen oxides and traces of hydrogen cyanide.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Spill: Evacuate spill area. With adequate ventilation and appropriate personal protective equipment, cover the area with an inert absorbent material such as clay or vermiculite and transfer to metal waste containers. Move container to a well ventilated area (outside), but do not seal the container with the isocyanate mixture. Larger quantities of liquid may be transferred directly to drums for disposal. Decontaminate or discard all clean-up equipment.

NOTE: ISOCYANATES WILL REACT WITH WATER AND GENERATE CARBON DIOXIDE. THIS COULD RESULT IN THE RUPTURE OF ANY CLOSED CONTAINERS.

Clean up: The area should then be flushed with a decontamination solution. The decontamination solution is a 5-10% mixture of sodium carbonate and 0.5% liquid detergent in water solution or a 3-8% concentrated ammonium hydroxide and 0.5% liquid detergent in water. Use 10 parts decontamination solution to 1 part spilled material.

If the ammonium hydroxide solution is used, ammonia will be evolved as a vapor. Use caution to avoid exposure to high concentrations of ammonia. Allow spill clean up to vent for 48 hours letting evolved carbon dioxide to escape.

SECTION 7. HANDLING AND STORAGE

Handling Precautions: Use personal protective equipment when transferring material to or from drums, totes or other containers. The reaction of polyols and isocyanates generates heat. Contact of the reacting materials with skin or eyes can cause irritation and may be difficult to remove from the affected areas. Immediately wash affected areas with plenty of water and seek medical attention. In addition, such contact increases the risk of exposure to isocyanate vapors. Do not smoke or use naked lights, open flames, space heaters, or other ignition sources near pouring, frothing or spraying operations.



2870 CRESTWOOD BLVD. STE B
 IRONDALE, AL 35210
 205-857-0040



DEFENDER

DEFENDER AP70 PART A
 SAFETY DATA SHEET

Special Emphasis for Spray Applications: Inspect the application area from the potential to expose other persons or for over-spray to drift onto buildings, vehicles or other property. When spraying building exteriors, persons entering or exiting the building as well as those inside could be exposed to polyisocyanates due to wind conditions, open windows or air intakes. Do not begin application work until these potential problems have been corrected.

Storage Requirements: When stored between 60°-85° F in sealed containers, typical shelf life is 6 months or more from the date of manufacture. Consult technical data sheet for shelf life requirements affecting performance quality. Should freezing occur, the material must be thawed completely and mixed until uniform. Opened containers must be handled properly to prevent moisture pickup.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: MDI has a low vapor pressure at room temperature. General/local ventilation typically control vapor levels very adequately. Uses requiring heating and/or spraying may require more aggressive engineering controls or PPE. Monitoring is required to determine engineering controls.

Personal Protective Equipment: HMIS PP, K | Full Face Respirator, Gloves, Full Suit, Boots

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: Complete suit protecting against chemicals. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Methylene bis(4-cyclohexylisocyanate) (5124-30-1) [30-40%]

Components with workplace control parameters

TWA 0.0050 ppm USA. ACGIH Threshold Limit Values (TLV)

Lower Respiratory Tract irritation. Respiratory sensitization.

C 0.01 ppm USA. OSHA- TABLE Z-1 Limits for Air Contaminants- 1910.1000
 0.11 mg/m3 Skin notation

C 0.01 ppm USA. NIOSH Recommended
 0.11 mg/m3 Exposure Limits



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART A
SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	NON-PIGMENTED LIQUID
PHYSICAL STATE	LIQUID
ODOR THRESHOLD	NO DATA AVAILABLE
SPECIFIC GRAV./DENSITY	N/A
VISCOSITY	NO DATA AVAILABLE
BOILING POINT	>350°F
FLAMMABILITY	NONE
PARTITION COEFFICIENT	NO DATA AVAILABLE
VAPOR PRESSURE	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
EVAP. RATE	<1
DECOM TEMP	NO DATA AVAILABLE
ODOR	MILD
SOLUBILITY	NOT SOLUBLE IN WATER, REACTS.
PERCENT VOLATILE	BY VOLUME, <1%; BY WEIGHT, <1%
FREEZING/MELTING POINT	NO DATA AVAILABLE
FLASH POINT	>250°F
VAPOR DENSITY	>1
AUTO-IGNITION TEMP	NO DATA AVAILABLE
UFL/LFL	NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability: Polyisocyanates are highly reactive chemicals and should be handled and stored in a way to avoid exposure to many common substances, including water and moisture. Material is stable when stored in sealed containers under normal conditions. Avoid extended exposure over 110°F (45°C).

Reactivity: Reacts with water, acids, bases, alcohols, metal compounds. The reaction with water is very slow under 120°F (50°C), but is accelerated at higher temperatures and in the presence of alkalis, tertiary amines and metal compounds. Some reactions can be vigorous or even violent.

Conditions to Avoid: Moisture and/or water. High temperatures, sparks, flame and extended exposure over 110°F (45°C).

Materials to Avoid: Acids; Alcohols; Bases; Metal compounds; Water.



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART A
SAFETY DATA SHEET

Hazardous Decomposition: Carbon dioxide - Excess gas may rupture containers.

Hazardous Polymerization: May occur with incompatible reactants, especially strong bases, water or temperatures over 320°F (50°C).

SECTION 11. TOXICOLOGICAL INFORMATION

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE) (5124-30-1) [30-40%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 9,900 mg/kg Remarks: Behavioral:Food intake (animal). Diarrhea Liver: Other changes.

LC50 Inhalation - rat - 4 h - 434 mg/m³

LD50 Dermal - rabbit - > 10,000 mg/kg

no data available

Skin corrosion/irritation: Skin - rabbit Result: Skin irritation - 24 h

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause respiratory irritation.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART A
SAFETY DATA SHEET

Additional Information: RTECS: NQ9250000

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea

Stomach - Irregularities - Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE) (5124-30-1) [30-40%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Danio rerio (zebra fish) - 1.2 mg/l - 96 h.

Persistence and degradability: Biodegradability Result: - Readily biodegradable.

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

DISPOSAL

Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance are the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Do not allow material to enter sewers, a body of water, or contact the ground. Refer to RCRA 40 CFR 261, and/or any other appropriate federal, state or local requirements for proper classification information.



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART A
SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

NA3082, Other regulated substances, liquid, n.o.s., 9, PGIII, (Hexamethylene-1,6-diisocyanate)

SECTION 15. REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Methylene bis(4-cyclohexylisocyanate) (5124-30-1) [30-40%] MASS, OSHAWAC, PA, SARA313, TSCA, TXAIR

Aliphatic isocyanate prepolymer blend (0) [55-60%] IARC

Regulatory CODE Descriptions

MASS = MA Massachusetts Hazardous Substances List

OSHA = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

SARA313 = SARA 313 Title III Toxic Chemicals

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level


IARC = IARC Carcinogen Risks

SECTION 16. OTHER INFORMATION

NFPA: Health = 2, Fire = 1, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 2, Fire = 1, Physical Hazard = 0

HMIS PPE: K - Full Face Respirator, Gloves, Full Suit, Boots



Disclaimer: Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

PRODUCT NAME	DEFENDER AP70 SIDE B
REVISION DATE	JUNE 2025
MANUFACTURER'S NAME	UMI COATINGS
ADDRESS	2870 CRESTWOOD BLVD. STE B IRONDALE, AL 35210
EMERGENCY PHONE	CHEMTREC: 800-424-9300 (ACCOUNT: CCN1022026)
INFORMATION PHONE NUMBER	205-857-0040

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

Health, Serious Eye Damage/Eye Irritation, 1
Health, Skin corrosion/irritation, 1 C
Environmental, Hazards to the aquatic environment - Acute, 3
Health, Skin corrosion/irritation, 2
Health, Carcinogenicity, 2
Health, Specific target organ toxicity - Single exposure, 3
Health, Acute toxicity, 4
Oral Health, Acute toxicity, 5
Dermal Environmental, Hazards to the aquatic environment - Acute, 2
Environmental, Hazards to the aquatic environment - Chronic, 3

GH LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

GHS SIGNAL WORD: **DANGER**

GHS HAZARD PICTOGRAMS:





2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

GHS HAZARD STATEMENTS

- H318** Causes serious eye damage
- H314** Causes severe skin burns and eye damage
- H402** Harmful to aquatic life
- H315** Causes skin irritation
- H351** Suspected of causing cancer
- H336** May cause drowsiness or dizziness
- H335** May cause respiratory irritation
- H302** Harmful if swallowed
- H313** May be harmful in contact with skin
- H401** Toxic to aquatic life
- H412** Harmful to aquatic life with long lasting effects

GHS PRECAUTIONARY STATEMENTS

- P201** Obtain special instructions before use.
- P202** Do not handle until all safety precautions have been read and understood.
- P260** Do not breathe dust/fume/gas/mist/vapors/spray.
- P273** Avoid release to the environment.
- P280** Wear protective gloves/protective clothing/eye protection/face protection.
- P281** Use personal protective equipment as required.
- P284** Wear respiratory protection.
- P302+350** IF ON SKIN: Gently wash with soap and water.
- P305+351+338** IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P308+313** IF exposed or concerned: Get medical advice/attention.
- P310** Immediately call a POISON CENTER or doctor/physician.
- P405** Store locked up.
- P501** Dispose of contents/container to a licensed waste disposal services provider.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS

Route of Entry Eyes; Ingestion; Inhalation; Skin

Target Organs Respiratory system; Skin; Eyes; Lungs

Inhalation Heating, spraying, foaming, or otherwise mechanically dispersing (drumming, venting or pumping) operations of this blend may generate more vapor or aerosol concentrations of its components. Amines can produce severe respiratory tract irritation. This will be experienced as a discomfort in the nose, throat and chest, with nasal discharge, cough, headache and difficulty with breathing. Prolonged or repeated contact may result in lung damage.



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

- Skin Contact** Prolonged contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.
- Eye Contact** Will cause irritation on contact. Symptoms from amine exposure include watering or discomfort of the eyes with marked excess redness and swelling. Severe exposure could produce chemical burns of the cornea.
- Ingestion**
Amines can cause severe irritation and possible chemical burns of the mouth, throat, esophagus and stomach with pain or discomfort in the mouth, throat, chest and abdomen. Symptoms include, nausea, vomiting, diarrhea, dizziness, thirst, circulatory collapse and coma. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

CAS	CHEMICAL NAME	% BY WEIGHT
0	Proprietary amine compounds	50% - 60%
13463-67-7	Titanium dioxide	1% - 10%
1333-86-4	Carbon black	0% - .5%
64852-22-8	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.' '-1,2,3-propanetriyltris[.omega.-(2-aminomethylethoxy)-	10% - 20%
9046-10-0	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethyl)-.omega.-(2-aminomethylethoxy)-	15-25%

SECTION 4. FIRST AID MEASURES

INHALATION

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility immediately.

SKIN CONTACT

Remove contaminated clothing immediately. Wash with large quantities of soap and water. Wash clothing before reuse. Seek medical attention if redness, burning or an itching sensation develops or persists after the area is washed.

EYE CONTACT

Flush eyes with plenty of water for at least 15 minutes. Use fingers to assure that the eyelids are separated and that the eye is being irrigated. Consult a physician.

INGESTION

Seek immediate medical attention. Immediately give two glasses of water. Do not induce vomiting unless prompted to do so by a medical professional. Never give anything by mouth to an unconscious person.



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE
PHYSICAL STATE
SPECIFIC GRAV./DENSITY
VISCOSITY
BOILING POINT
FLAMMABILITY
VAPOR PRESSURE
EVAP. RATE
ODOR
MOLECULAR FORMULA
SOLUBILITY
PERCENT VOLATILE
FREEZING/MELTING POINT
FLASH POINT
VAPOR DENSITY
AUTO-IGNITION TEMP

SECTION 10. STABILITY AND REACTIVITY



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

Carbon black (1333-86-4) [0-.5%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - male and female - > 8,000 mg/kg (OECD Test Guideline 401)

Inhalation: no data available

LD50 Dermal - rabbit - > 3,000 mg/kg Skin corrosion/irritation: Skin - rabbit Result: No skin irritation - 24 h (OECD Test Guideline 404) Serious eye damage/eye irritation: Eyes - rabbit Result: No eye irritation (OECD Test Guideline 405) Respiratory or skin sensitization: - guinea pig Result: Did not cause sensitization on laboratory animals. (OECD Test Guideline 406) Germ cell mutagenicity: Ames test *S. typhimurium* Result: negative Hamster ovary DNA repair rat - female Carcinogenicity:

Carcinogenicity - rat - Inhalation:

Tumorigenic: Carcinogenic by RTECS criteria. Lungs, Thorax, or Respiration: Tumors. This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Carbon black)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: FF5800000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

**Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-
(9046-10-0) [15-25%]**

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 2,885.3 mg/kg

Inhalation LC50 LC50 Inhalation - rat - 8 h - > 0.74 mg/l

Dermal LD50 LD50 Dermal - rabbit - 2,980 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation Skin - rabbit - Corrosive, category 1C - where responses occur after exposures between 1 hour and 4 hours an observations up to 14 days. - OECD Test Guideline 40

Serious eye damage/eye irritation Eyes - rabbit - Corrosive to eyes - OECD Test Guideline 40

Respiratory or skin sensitization

Germ cell mutagenicity Animal testing did not show any mutagenic effect

Genotoxicity in vitro - Not mutagenic in Ames Test

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified a probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by OSHA.



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

Reproductive toxicity

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: Potential health effect

Inhalation: May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.

Ingestion: May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin burns. Eyes Causes eye burns.

Signs and Symptoms of Exposure Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin.

Cough Shortness of breath, Headache, Nausea

Synergistic effect

Additional Information

Repeated dose toxicity - rat - Dermal - No observed adverse effect level - 250 mg/kg

Repeated dose toxicity - rat - Oral - No observed adverse effect level - 239 mg/kg

RTECS: Not available

SECTION 12. ECOLOGICAL INFORMATION

Carbon black (1333-86-4) [0-.5%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Danio rerio (zebra fish) - > 1,000 mg/l - 96 h

Toxicity to daphnia and static test EC50 - Daphnia magna (Water flea) - > 5,600 mg/l - 24 h. other aquatic (OECD Test Guideline 202) invertebrates

Toxicity to algae static test EC50 - Desmodesmus subspicatus (green algae) - > 10,000 mg/l -: 72 h (OECD Test Guideline 201)



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

**Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-
(9046-10-0) [15-25%]**

Information on ecological effects

Toxicity:

Toxicity to fish semi-static test LC50 - *Oncorhynchus mykiss* (rainbow trout) - > 15 mg/l - 96 h.

static test NOEC - *Oncorhynchus mykiss* (rainbow trout) - 15 mg/l - 96 h

Toxicity to daphnia static test EC50 - *Daphnia* - 80 mg/l - 48 h. and other aquatic Method: OECD Test Guideline 202 invertebrates

NOEC - *Daphnia* - 18 mg/l - 48 h

Persistence and degradability:

Biodegradability Result: 0 % - According to the results of tests of biodegradability this product is not readily biodegradable.
Method: OECD Test Guideline 301B

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.



2870 CRESTWOOD BLVD. STE B
 IRONDALE, AL 35210
 205-857-0040



DEFENDER

DEFENDER AP70 PART B
SAFETY DATA SHEET

SECTION 13. DISPOSAL CONSIDERATIONS

DISPOSAL

Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance are the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Do not allow material to enter sewers, a body of water, or contact the ground. Refer to RCRA 40 CFR 261, and/or any other appropriate federal, state or local requirements for proper classification information.

SECTION 14. TRANSPORT INFORMATION

UN2735, Amines, liquid, corrosive, n.o.s, or Polyamines, liquid, corrosive, n.o.s., 8, PGII, (Polyoxypropylenediamine)

SECTION 15. REGULATORY INFORMATION

CAS	Chemical Name	% by Weight	Regulation List
13463-67-7	Titanium dioxide	1-10%	IARC, MASS, OSHAWAC, PA, TSCA, TXAIR
64852-22-8	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.,.alpha.',.alpha.' '-1,2,3-propanetriyltris [.omega.-(2-aminomethylethoxy)	10-20%	TSCA
9046-10-0	Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethyl)-.omega.-2-aminomethylethoxy)	15-25%	TSCA

Regulatory CODE Descriptions

-
- IARC = IARC Carcinogen Risks
 - MASS =MA Massachusetts Hazardous Substances List
 - OSHA = OSHA Workplace Air Contaminants
 - PA = PA Right-To-Know List of Hazardous Substances
 - TSCA = Toxic Substances Control Act
 - TXAIR =TX Air Contaminants with Health Effects Screening Level



2870 CRESTWOOD BLVD. STE B
IRONDALE, AL 35210
205-857-0040



DEFENDER


DEFENDER AP70 PART B
SAFETY DATA SHEET

SECTION 16. Other Information

NFPA: Health = 2, Fire = 1, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 2, Fire = 1, Physical Hazard = 0

HMIS PPE: K - Full Face Respirator, Gloves, Full Suit, Boots



DISCLAIMER

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).